



WATERTRUST PRO SERIES™ WHOLE HOUSE CARBON FILTRATION SYSTEM

POINT
OF
ENTRY



COUNT ON THE PENTAIR WATERTRUST PRO SERIES

Treat water confidently with the reliable and industry proven Pentair WaterTrust Pro Series. Simple installation, service, and a wide range of applications makes the WaterTrust Pro Series your go-to choice for water softening and filtration.

FEATURES • BENEFITS

- ◆ Newly redesigned and industry-proven technology delivers high performance and simple operation.
- ◆ Carbon filtration provides cleaner, fresher water throughout the whole home.
- ◆ Trade professional ready – installation is straightforward and efficient with easily accessible parts.
- ◆ With quick start-up settings and automatic calculations, simply set up and go.

INSTALLATION • MAINTENANCE

Installation Considerations

- ◆ When installing the system where the environment is extremely hot or cold, precautions must be taken to protect the system from the elements.
- ◆ Install on cold water lines only.
- ◆ When a filter and a softener are installed together, it is preferred to run a separate drain line from each unit to the point of termination.

Maintenance

- ◆ Periodically clean the backwash flow control.
- ◆ Verify the minimum and maximum water pressure. Install a pressure reducer if necessary.

More detailed installation and service instructions can be found in the user manual.

APPLICATIONS

Household Size*

- ◆ 35977: 1-4 occupants
- ◆ 35978: 4-6 occupants
- ◆ 35979: 6-8 occupants

Water Source

- ◆ City or Well

REDUCES



Chlorine
Taste & Odor



Systems Tested and Certified by WQA Under NSF/ANSI/CAN 61 for Material Safety and NSF/ANSI 372 for Lead Free Compliance Only

**Based on typical home water usage and flow rates but will vary by consumer*

WHOLE HOUSE CARBON FILTRATION SYSTEM

POINT
OF
ENTRY

Product Number	35977	35978	35979
Chlorine Capacity (gallons)	400,000	600,000	800,000
Max Flow Rate (gal/min)	11.6	11.9	13.2
Drain Flow Rate (gal/min)	5	5	7
Working Pressure (psi)	20 - 120	20 - 120	20 - 120
Operating Water Temperature	40 - 100° F	40 - 100° F	40 - 100° F
Electrical Rating	Input: 120V AC Output: 12V AC	Input: 120V AC Output: 12V AC	Input: 120V AC Output: 12V AC
Resin Amount (cu. ft.)	1	1.5	2
Resin Tank Size (dia x h) (includes valve head)	10.2" x 51.6"	10.2" x 61.6"	12.2" x 55.6"

Service Parts

Part Number	Part
1041174	Flappers Service Kit

Spare Parts

Part Number	Part
1235339	Valve Disc Spring, One Piece
3019221	Motor/Optical Cable Assembly
1040930	Valve Bypass
1235446	Turbine Cable
1033444	Internal Turbine Meter
1242168	762 Controller (Softener / Tannin)
1242162	742 Controller (Carbon / PH filters)



13845 Bishops Dr. | Suite 200 | Brookfield, WI 53005 | United States
P: 262.238.4400 | Customer Service: 800.279.9404 | tech-support@pentair.com | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.
©2023 Pentair. All Rights Reserved.

4007155 Rev A 0C23